

Sunlight Readable LCD

Sunlight Readable LCD



26" (16:9)

Specifications

RoHS
COMPLIANT
2002/95/EC

Model Name	W26L100-CHA2TR
Viewable Size Image	26"(16:9)
Active Display Area(mm)	575.769(H)x323.712(V)
Pixel Pitch(mm)	0.4215(H)x0.4215(V)
Number of Pixels	1366x768
Contrast Ratio	800:1(typ.)
Display Color	16.7M(8bit/colors)
Brightness(cd/m ²)	625
Viewing Angle(CR>=10)	-88~88(H);-88~88(V)
Synchronization Range	31.5~60KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	1366x768@60Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	145W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	SAW
Optional protection glass(reflection rate<0.5%)	Optional

Outdoor readability

Ambient light(nit)	Brightness measure Angle	10,000	30,000	80,000
Brightness gain(BLoff)(nit)	35°	625	820	1,200
Reflectance(net)(%)		1.00%	0.98%	0.9%

Remarks:W26L100series= VGA Input only

W26L110 series=VGA+Video Input

Mechanical Drawing

